



Grout

by hemway.

Premium Ready-Mixed Fix & Grout

A premium grade fungal resistant waterproof ceramic tile adhesive and grout. Designed to permanently fix and grout ceramic wall tiles in areas subject to prolonged damp conditions.

Applications

- ✓ Kitchen
- ✓ Bathroom

Features

- ✓ 6 Colours
- ✓ Ready-Mixed
- ✓ High-Grade Acrylic
- ✓ Non-Shrink
- ✓ Eco-Friendly
- ✓ Vegan & Cruelty-Free
- ✓ Mould Resistant
- ✓ Water Resistant¹
- ✓ UV Resistant
- ✓ Non-Toxic

Preparation

Before starting, make sure all tiling surfaces are dry, clean, and free from dust or grease. Additionally, if you are working with very porous surfaces, apply an acrylic primer and allow it to dry completely.

For timber or wood surfaces exposed to water contact, treat them with a water-resistant sealer. It is also essential to test the grout on a sample tile to avoid staining, particularly with satin, matte, or metallic finishes.

Cleaning

Tools should be washed with water immediately after use.

Hemway Ready-Mixed Grout contains acticide to protect against mould. To maintain its appearance, clean the grout lines regularly with an antibacterial cleaner.

Uses

Ready to use adhesive and grout, ideal for fixing and grouting tiles in kitchens, bathrooms, toilets and showers. It is suitable for use on: gypsum plaster; concrete render; brick; plywood; blockboard; fibre cement sheet; glazed tiles and most common building materials.

Flammability	Non-Flammable
Composition	Synthetic Emulsion Resin With Inorganic Fillers
Appearance	Stiff Paste
Application Temperature	Between 5°C and 30°C
Coverage	2-3 Kg / m ²
Max Bed Depth	3mm
Open Time	Approx. 20 Minutes
Full Set Time	Approx. 24 - 48 Hours
Density	Approx. 1.7g / cm ³
Low VOC	< 0.1%
Storage	Between 5°C and 30°C ²
Shelf Life	Min. 12 Months ³

Not recommended for use on floors or areas subject to continuous water immersion e.g. swimming pools, ponds and external use, porcelain tiles, large format tiles, or for use where the ambient temperature is below +5°C. May cause discolouration of some types of marble.

Do not leave empty containers where residue could be harmful to children, animals or the environment. Remove any tubs or used material to a central disposal point in accordance with local regulations.

Commodity Code 3816000000.

¹ Ready-Mixed Fix & Grout exceeds the requirements of BS5980 (1980) Type 2 Water Resistant Class AA and BSEN 12004 Type D2.

² Store in cool, dry conditions. Protect from frost and keep out of direct sunlight.

³ From date of manufacture when stored in original, sealed containers.