

## PRODUCT NAME

Hemway Clear Matt Lacquer

## ORIGINALLY ISSUED

01/02/2025

## PRODUCT CODE

HEMMATT

## VERSION

1.0

## VERSION DATE

01/02/2025



### PRODUCT DESCRIPTION

Clear Matt Lacquer is designed to perfect and protect current painted surfaces to prevent stains, marks, colour fade and any unwanted wear and tear of a chalk paint finished surface. Clear Matt Lacquer can be used both internally or externally giving the user variability. In a 'Matt' low sheen finish, Clear Matt Lacquer is the latest addition to the Hemway's Lacquer product portfolio which gives an uber modern and classic feel, and not to disappoint it delivers long-lasting tough wearing perfect results time after time.



### IMPORTANT INSTRUCTIONS BEFORE USE

- Read and follow SDS, TDS and label instructions
- Stir all paints thoroughly before use
- Check colour & sheen.
- Reduce emissions and maintain quality by replacing tin lid after use



### MAXIMUM VOC CONTENT (RFU)

0.11Kg/L

### REGULATIONS / COMPLIANCE

- 2004/42 IIA WB (D) 130



### COLOUR RANGE

•



### GENERAL INFORMATION

Coverage 12 square metres per litre @ 30 microns dft  
Flashpoint 103°C  
Storage Store between 5°C - 25°C. When not in use, cans must be kept sealed  
Shelf Life 12 months from delivery date in original sealed containers



### CLEANING

Ensure your desired surface area is clean, free from wax, oil and fully dry. Carry out a sample test in a small area first, this will ensure it meets your expectations before carrying out your full project.



### SURFACE PREPARATION

With the lid securely on, shake the tin well, then stir the contents of this tin with a thin spatula. This will ensure an even mixture is accomplished. We recommend using a brush or roller. Load your applicator with Clear Matt Lacquer, and then remove excess before applying. If using a brush, use a 2-3 inch paintbrush, applying a crisscross motion to give an even spread. Allow 1 hour to dry between coats.



### ADDITIONAL INFORMATION





### HEALTH AND SAFETY

- Refer to SDS and tin label prior to use.

## APPLICATION METHODS

	BRUSH	ROLLER	COMPLIANT SPRAY GUN	
<b>MIXING RATIO</b>				
RFU	RFU		Base Thinner	51r >10%
<b>THINNER OPTIONS</b>			Water	Water
<b>VISCOSITY</b>	As supplied	As supplied		As supplied
<b>NUMBER OF COATS (GUIDE ONLY)</b>	1-2 Coats	1-2 Coats	1-2 Coats	
<b>FLASH OFF</b>				
<b>DRYING TIME</b>	Touch dry Hard dry	30mins @20°C 24 hours	Touch dry Hard dry	30mins @20°C 24 hours
<b>RECOATABILITY / OVERCOATING</b>	16hrs minimum 14days maximum	16hrs minimum 14days maximum	16hrs minimum 14days maximum	

	<b>WET FILM THICKNESS*</b>			
	80microns	80microns	80microns	
	<b>DRY FILM THICKNESS*</b>			
	30microns	30microns	30microns	
<p><small>* Hemway Technical Data Sheets indicate a Dry Film Thickness that will be achieved when applying a particular Wet Film Thickness. These values are a guide only and are not to be used as specifications. Film thickness will vary depending on actual use and specification. Great care should be taken to achieve the dft stated in the agreed specification and to avoid areas of excessively low or high thickness.</small></p>				

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of Hemway's knowledge and belief accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use.